



Return to Load

- High Capacity Spray System
- Compressed Air Blow-off with Optional High Volume Heated Pressure Blow-off
- Variable Speed Table Drive
- Single-Part Continuous Feed Operation
- Common Point Load & Unload
- Robot Load/Unload
- Solution Filtration
- Stainless Steel Construction
- Small Foot-Print

Cell-U-Clean - Series RTL

All specifications are subject to change without notice



CLEANING TECHNOLOGIES GROUP

RANSOHOFF BLACKSTONE-NEY ULTRASONICS CTG ASIA

MODEL NUMBER	RTL
Production Rate	120 Parts per Hour
WORKING ENVELOPE (L x W x H)	6" x 6" x 12"
WORKING ENVELOPE (L x W x H)	305mm x 153mm x 153mm
LOAD HEIGHT	39" (990mm)
WASH TANK CAPACITY	180 Gallons (684 Liters)
PART WEIGHT	40lbs (18kg) Per Platter
CONTROLS	Siemens PLC and HMI
FLOOR SPACE (LXWXH)	8.0' X 5.0' X 6' 8" (2440mm x 1525mm x 2030mm)
UTILITY REQUIREMENTS	460V 3 Ph, 60 Hz

Ransohoff

(800) 248-9274
4933 Provident Drive
Cincinnati, OH 45246
www.ctgclean.com

Blackstone-NEY Ultrasonics

(800) 766-6606
P.O. Box 220
9 N. Main St.
Jamestown, NY 14702-0220

CTG Asia

(86)0512-66161698
56 Songshan Road
Suzhou New District
Jiangsu Province, China PRC: 215151