



## MultiSONIK<sup>®</sup>3

- Standard frequencies: 40, 72 and 104 kHz in one process tank.
- Max Power Output: 240-960W
- Input voltage: 208, 220 or 240 Volt 1 Ph, 50/60 Hz (depending on generator model)
- Power Control: Adjust function controls output from 10 to 100% power adjustment via analog dial or PLC control
- Optional PLC Controller with Built-in HMI for Frequency and Power Selection
- Power control 0 - 10 Volt DC analog input
- Power meter 0 - 10 Volt DC analog input
- 24 Volt Remote On/Off
- 24 Volt Binary Frequency Select
- Has full amplitude, sweep function over a 4-6kHz bandwidth
- Patented dualSWEEP<sup>®</sup> and upSWEEP<sup>®</sup> technology, can operate at frequencies of 40, 72, and 104
- FCC, CE, SOP 39 Compliant
- Dimensions: 11.25" LR X 15" FB X 6.125" high

# MultiSONIK<sup>®</sup> 3

## THREE FREQUENCY GENERATOR

All specifications are subject to change without notice

**Blackstone-NEY Ultrasonics**  
 (800) 766-6606  
 P.O. Box 220  
 9 N. Main St.  
 Jamestown, NY 14702-0220  
[www.ctgclean.com](http://www.ctgclean.com)

**Ransohoff**  
 (800) 248-9274  
 4933 Provident Drive  
 Cincinnati, OH 45246

**CTG Asia**  
 (86)0512-66161698  
 56 Songshan Road  
 Suzhou New District  
 Jiangsu Province, China PRC: 215151



CLEANING TECHNOLOGIES GROUP

RANSOHOFF • BLACKSTONE-NEY ULTRASONICS • CTG ASIA